

Qualified Glulam and CLT Products With Low Formaldehyde Emissions

PR-E740

Revised September 29, 2016

Product: Glulam and CLT Products Qualified for Low Formaldehyde Emissions

1. Basis of the product report:
 - APA Custom Product Specification E-740
 - Test method follows the principles of ISO 12460-4, Wood-Based Panels -- Determination of Formaldehyde Release, Part 4: Desiccator Method, and AS/NZS 4357.4:2005, Structural Laminated Veneer Lumber, Part 4: Determination of Formaldehyde Emissions
 - 2015, 2012 and 2009 International Building Code (IBC): Section 2303.1.3 Structural glued laminated timber
 - 2015 IBC: Section 2303.1.4 Structural Glued Cross-Laminated Timber
 - 2012 and 2009 IBC: Section 104.11 Alternative materials
 - 2015 International Residential Code (IRC): Sections R502.1.3, R602.1.3, and R802.1.2 Structural glued laminated timber, and Sections R502.1.6, R602.1.6 and R802.6 Cross-Laminated Timber
 - 2012 and 2009 IRC: Sections R502.1.5, R602.1.2, and R802.1.4 Structural glued laminated timber, and Section R104.11 Alternative materials, respectively
 - ASTM D3737-12, D3737-08, and D3737-07 recognized by the 2015 IBC and IRC, 2012 IBC and IRC, and 2009 IBC and IRC, respectively
 - ANSI A190.1-2012 and ANSI/AITC A190.1-2007 recognized by the 2015 IBC and IRC, and 2012 IBC and IRC and 2009 IBC and IRC, respectively
 - ANSI/APA PRG 320-2012 and PRG 320-2011 Performance Rated Cross-Laminated Timber
 - APA Report (see Table 2) and other qualification data

2. Product description:

Glulam products are manufactured with layup combinations documented in ANSI 117, or the in-plant manufacturing standard and approved by APA. Glulam products are available in a variety of sizes. CLT products are manufactured with grade characteristics specified in ANSI/APA PRG-320 and are available in a variety of sizes.

3. Formaldehyde emission level:

The G-5 rating is a formaldehyde emission level as defined in Table 1. Glulam products have been qualified for low formaldehyde emissions following the principles of ISO 12460-4 and AS/NZS 4357.4:2005, and the performance requirements of ANSI A190.1 or CSA O122. Glulam products meeting the formaldehyde emission level specified in Table 1 in accordance with the APA Custom Product Specification E-740 are listed in Table 2.

Table 1. Upper formaldehyde emission level for G-5 rating following the principles of ISO 12460-4 and AS/NZS 4357.4:2005^(a)

Average	0.20 mg/ℓ
Individual specimen	0.30 mg/ℓ

^(a) Glulam products meeting ANSI A190.1 and CLT meeting ANSI/APA PRG 320 are not within the scope of the CARB and HUD regulations. The tabulated formaldehyde emission level in the G-5 standard is more stringent than the E₀ of AS/NZS 4357.4:2005 and F☆☆☆☆ of JAS Standard for Glulam, MAFF Notification 1152.

4. Limitations:
 - a) Glulam and CLT products shall be designed and installed in accordance with the applicable provisions of the code and the recommendations provided by the manufacturer.
 - b) Glulam and CLT products are limited to dry service conditions that result in the average equilibrium moisture content of sawn lumber of less than 16 percent.
 - c) Glulam and CLT products are produced by the manufacturing facility shown in Table 2 under a quality assurance program audited by APA in accordance with the APA Custom Product Specification E-740.
 - d) This report is subject to re-examination in one year.

5. Identification:

Glulam and CLT products are identified by a label bearing the manufacturer's name and/or trademark, the APA assigned plant number, the product standard (ANSI A190.1 or CSA O122 for glulam, and ANSI/APA PRG 320 for CLT), the combination symbol for glulam or grade designation for CLT, the APA logo, the product report number PR-E740, and the formaldehyde emission rating G-5.

Table 2. Qualified Manufacturing Facility for Low Formaldehyde Emission

Manufacturer	Location	Mill Number	APA Test Report
Boise Cascade Company	Homedale, ID	1107	T2015Q-31
Nordic Structures (Glulam)	Chibougamau, QC	1057	T2016P-7
Nordic Structures (CLT)	Chibougamau, QC	1112	T2016P-7

APA – The Engineered Wood Association is an approved national standards developer accredited by American National Standards Institute (ANSI). APA publishes ANSI standards and Voluntary Product Standards for wood structural panels and engineered wood products. APA is an accredited certification body under ISO/IEC 17065 by Standards Council of Canada (SCC), an accredited inspection agency under ISO/IEC 17020 by International Code Council (ICC) International Accreditation Service (IAS), and an accredited testing organization under ISO/IEC 17025 by IAS. APA is also an approved Product Certification Agency, Testing Laboratory, Quality Assurance Entity, and Validation Entity by the State of Florida, and an approved testing laboratory by City of Los Angeles.

**APA – THE ENGINEERED WOOD ASSOCIATION
HEADQUARTERS**

7011 So. 19th St. ▪ Tacoma, Washington 98466
Phone: (253) 565-6600 ▪ Fax: (253) 565-7265 ▪ Internet Address: www.apawood.org

PRODUCT SUPPORT HELP DESK
(253) 620-7400 ▪ *E-mail Address:* help@apawood.org

DISCLAIMER

APA Product Report® is a trademark of *APA – The Engineered Wood Association*, Tacoma, Washington. The information contained herein is based on the product evaluation in accordance with the references noted in this report. Neither APA, nor its members make any warranty, expressed or implied, or assume any legal liability or responsibility for the use, application of, and/or reference to opinions, findings, conclusions, or recommendations included in this report. Consult your local jurisdiction or design professional to assure compliance with code, construction, and performance requirements. Because APA has no control over quality of workmanship or the conditions under which engineered wood products are used, it cannot accept responsibility for product performance or designs as actually constructed.