

## Standard Dimensions, Nordic Lam

### STANDARD DIMENSIONS

Product:

Width (mm):

Depths (mm):

Nordic Lam Architectural 24F-ES/NPG						
44	86	137	184	228	279	327
70	127	137				
95	178	178	184			
121	222	222	222	228		
146	267	267	267	267	279	
171	318	318	318	318	318	327
197	362	362	362	362	362	362
222	406	406	406	406	406	406
248	457	457	457	457	457	457
273	502	502	502	502	502	502
298	546	546	546	546	546	546
324	597	597	597	597	597	597
349	641	641	641	641	641	641
375	686	686	686	686	686	686
400	737	737	737	737	737	737
425	781	781	781	781	781	781
451	826	826	826	826	826	826
	870	870	870	870	870	870
	921	921	921	921	921	921
	965	965	965	965	965	965
	1010	1010	1010	1010	1010	1010
		1054	1054	1054	1054	1054
		1105	1105	1105	1105	1105
		1149	1149	1149	1149	1149
		1194	1194	1194	1194	1194
		1245	1245	1245	1245	1245
		1289	1289	1289	1289	1289
		1334	1334	1334	1334	1334
		1384	1384	1384	1384	1384
		1429	1429	1429	1429	1429
		1473	1473	1473	1473	1473
		1524	1524	1524	1524	1524
		1568	1568	1568	1568	1568
		1613	1613	1613	1613	1613
			1664	1664	1664	1664
			1708	1708	1708	1708
			1753	1753	1753	1753
			1797	1797	1797	1797
			1848	1848	1848	1848
			1892	1892	1892	1892
			1937	1937	1937	1937
			1981	1981	1981	1981
			2032	2032	2032	2032
			2076	2076	2076	2076
			2121	2121	2121	2121
			2172	2172	2172	2172
				2216	2216	2216
				2261	2261	2261
				2311	2311	2311
				2356	2356	2356
				2400	2400	2400

Notes:

1. The depth-to-width ratio shall be limited to 12:1.
2. The dimensions showed in black are the optimum dimensions for straight beams (maximum length of 18.9 m).
3. Beams of dimensions in light grey are fabricated using manual techniques (maximum length of 24.4 m).
4. Arched beams are available in dimensions up to 327 mm x 2400 mm x 24.0 m (width x depth x length).
5. Other dimensions are available on request; please contact Nordic.

## Standard Dimensions, Nordic Lam

### STANDARD DIMENSIONS, IMPERIAL UNITS

Product:  
Width (in.):  
Depths (in.):

Nordic Lam Architectural 24F-ES/NPG						
1 3/4	3 3/8	5 3/8	7 1/4	9	11	12 7/8
2 3/4	5	5 3/8				
3 3/4	7	7	7 1/4			
4 3/4	8 3/4	8 3/4	8 3/4	9		
5 3/4	10 1/2	10 1/2	10 1/2	10 1/2	11	
6 3/4	12 1/2	12 1/2	12 1/2	12 1/2	12 1/2	12 7/8
7 3/4	14 1/4	14 1/4	14 1/4	14 1/4	14 1/4	14 1/4
8 3/4	16	16	16	16	16	16
9 3/4	18	18	18	18	18	18
10 3/4	19 3/4	19 3/4	19 3/4	19 3/4	19 3/4	19 3/4
11 3/4	21 1/2	21 1/2	21 1/2	21 1/2	21 1/2	21 1/2
12 3/4	23 1/2	23 1/2	23 1/2	23 1/2	23 1/2	23 1/2
13 3/4	25 1/4	25 1/4	25 1/4	25 1/4	25 1/4	25 1/4
14 3/4	27	27	27	27	27	27
15 3/4	29	29	29	29	29	29
16 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4	30 3/4
17 3/4	32 1/2	32 1/2	32 1/2	32 1/2	32 1/2	32 1/2
	34 1/4	34 1/4	34 1/4	34 1/4	34 1/4	34 1/4
	36 1/4	36 1/4	36 1/4	36 1/4	36 1/4	36 1/4
	38	38	38	38	38	38
	39 3/4	39 3/4	39 3/4	39 3/4	39 3/4	39 3/4
		41 1/2	41 1/2	41 1/2	41 1/2	41 1/2
		43 1/2	43 1/2	43 1/2	43 1/2	43 1/2
		45 1/4	45 1/4	45 1/4	45 1/4	45 1/4
		47	47	47	47	47
		49	49	49	49	49
		50 3/4	50 3/4	50 3/4	50 3/4	50 3/4
		52 1/2	52 1/2	52 1/2	52 1/2	52 1/2
		54 1/2	54 1/2	54 1/2	54 1/2	54 1/2
		56 1/4	56 1/4	56 1/4	56 1/4	56 1/4
		58	58	58	58	58
		60	60	60	60	60
		61 3/4	61 3/4	61 3/4	61 3/4	61 3/4
		63 1/2	63 1/2	63 1/2	63 1/2	63 1/2
		65 1/2	65 1/2	65 1/2	65 1/2	65 1/2
		67 1/4	67 1/4	67 1/4	67 1/4	67 1/4
		69	69	69	69	69
		70 3/4	70 3/4	70 3/4	70 3/4	70 3/4
		72 3/4	72 3/4	72 3/4	72 3/4	72 3/4
		74 1/2	74 1/2	74 1/2	74 1/2	74 1/2
		76 1/4	76 1/4	76 1/4	76 1/4	76 1/4
		78	78	78	78	78
		80	80	80	80	80
		81 3/4	81 3/4	81 3/4	81 3/4	81 3/4
		83 1/2	83 1/2	83 1/2	83 1/2	83 1/2
		85 1/2	85 1/2	85 1/2	85 1/2	85 1/2
				87 1/4	87 1/4	87 1/4
				89	89	89
				91	91	91
				92 3/4	92 3/4	92 3/4
				94 1/2	94 1/2	94 1/2

Notes:

1. Depth-to-width ratio shall be limited to 12:1.
2. Dimensions shown in black are the optimum dimensions for straight beams (maximum length of 62 ft).
3. Beams of dimensions in light grey are fabricated using manual techniques (maximum length of 80 ft).
4. Arched beams are available in dimensions up to 12-7/8 in. x 94-1/2 in. x 78 ft 9 in. (width x depth x length).
5. Other dimensions are available on request; please contact Nordic.